

NOVA KOOL

Single Door Refrigerators

- ◆ These units have a large interior volume with a small cut out dimension
- ◆ Large reversible doors, with magnetic gaskets for a positive seal
- ◆ All stainless steel hinges
- ◆ Construction is rugged 18 gauge epoxy coated satin coat steel frame with a galvanized steel outer cabinet shell
- ◆ The interior lining is made of impact resistant polystyrene plastic with solid fill urethane insulation
- ◆ Thermostat controlled for a wide range of settings
- ◆ Low draw fan comes standard
- ◆ The removable door panel can be replaced to match differing interiors
- ◆ Standard freezer compartments with doors and ice tray, except the R2600
- ◆ Compressor automatically shuts down in low voltage conditions
- ◆ If using an AC/DC unit, it automatically switches to AC when AC power is available
- ◆ Designed for marine use, they can operate at a constant angle of up to 30 degrees
- ◆ The quiet DC compressor will not interfere with other equipment, when operated solely on DC voltage



R1900



R2300



R2600



R3000/R3800



R4500



R5810

| Part # | Volume Cu Ft (ltrs) | Freezer Cu Ft (ltrs) | Light | Volts | Power Amps/24H* | Cutout H x W x D in. | Weight lbs |
|--------------------------------|------------------------|-------------------------|-------|---------------------------------------|--------------------|-----------------------------|---------------|
| NOV R1900 DC NOV R1900ACDC | 1.9 (54) | 0.21 (6.0) | N/A | 12/24 VDC 12/24 & 100/240 50/60 Hz | 23.75 @ 12V | 20-5/8" x 15-5/8" x 17-3/4" | 40 |
| NOV R2300 DC | 2.1 (59) | 0.25 (7.0) | N/A | 12/24 VDC | 29.2 @ 12V | 28-3/8" x 16-3/4" x 14" | 45 |
| NOV R2600 DC NOV R2600ACDC | 2.4 (68) | 0.14 (4.0) | N/A | 12/24 VDC 12/24 & 100/240 50/60 Hz | 23.75 @ 12V | 20-1/4" x 18" x 19-1/2" | 39 |
| NOV R3000DC-W NOV R3000ACDC | 2.5 (70) | 0.25 (7.1) | N/A | 12/24 VDC | 27 @ 12V | 24-5/8" x 19-1/4" x 15-1/2" | 45 |
| NOV R3100 DC | 3.0 (85) | 0.3 (8.5) | N/A | 12/24 VDC | 29.2 @ 12V | 28-3/8" x 16-3/4" x 19-1/2" | 48 |
| NOV R3800 DC NOV R3800ACDC | 3.5 (100) | 0.45 (12.7) | Yes | 12/24 VDC 12/24 & 100/240 50/60 Hz | 30 @ 12V | 28-3/8" x 20-1/4" x 18" | 54 |
| NOV R4500 DC NOV R4500ACDC | 4.3 (122) | 0.6 (17.0) | Yes | 12/24 VDC 12/24 & 100/240 50/60 Hz | 35.8 @ 12V | 28-3/8" x 20-1/4" x 21" | 59 |
| NOV R5810 DC NOV R5810ACDC | 5.8 (164) | 0.4 (11.3) | Yes | 12/24 VDC 12/24 & 100/240 50/60 Hz | 50 @ 12V | 31-7/8" x 23-1/8" x 23-3/4" | 69 |

*Consumption is based on amps over a 24 hour period and calculated based on normal use at 75°F (23°C) ambient temperature, and a 39°F (4°C) refrigerator temperature.